

Connor Sports Neoshok

Neoshok is an area elastic premium solid hardwood floating studio floor system with high resistance and uniformity, consisting of a vapour barrier two stage polyurethane Neoshok pads, two layers of APA subfloor - plywood, maple flooring with the option for sanding, sealers, finishers, game lines and wall base.

All systems have been tested to the international standard EN 14904 - 2006.

Installation should be carried out in accordance Gerflor recommendations, Subfloor comply with the BS8203/8204 standards, to be smooth, hard, clean, flat and of sound construction and dry prior to laying.

Consult with Gerflor Ltd for technical details and to obtain samples.

Profile: Hardwood Maple Strip

Manufacturer and reference: Gerflor Ltd, Wedgnock House, Wedgnock Lane, Warwick, CV34 5AP. Tel: 01926 622600, Fax: 01926 401647

Email: contractuk@gerflor.com

Reference: Connor Sports Neoshok

Pads: Red Neoshok pads, 70 durometer urethane pads

Thickness: 63 mm

Colour: MFMA approved Maple wood available in 3 colour grades

Dimension: 20 mm thick x 57 mm wide x random length

Fixing: As per manufacturers instruction

Abrasion resistance: 0.07

Shock absorption: ≥ 25

Ball bounce: ≥ 90

Sliding Coefficient: 80-110

Post Installation Maintenance: Sweep clean, remove any debris from the surface.

Regular Maintenance: Sweep clean.