

DESCRIPTION

Total thickness	EN 428	mm	6.00
Weight	EN 430	g/sq.m	9365
Thickness of Wearlayer	EN 429	mm	2
Tile size	EN 427	mm	635 x 635

CLASSIFICATION

Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
Fire rating	AS ISO9239-1	kW/m2	9.3
		smoke%/min	384
Slip resistance - Wet Pendulum	AS 4586-2013 (App A)	group	P3
Static electrical propensity	EN 1815	kV	< 2

PERFORMANCE

Wear resistance	EN 660.2	mm ³	≤ 2.0
Wear Group	EN 649	group	T
Type Binder content	ISO 10581	type	I
Dimensional stability	EN 434	%	≤ 0.25
Residual indentation	EN 433	mm	≤ 0.10
Castor chair test (type W)	EN 425	-	OK
Shore Hardness	EN ISO 868	H _D	≥ 55
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	PUR+
Chemical products resistance (1)	EN 423	class	OK

ENVIRONMENT / INDOOR AIR QUALITY

VOC	ASTM D5116	mg/m2/hr (24hours)	< 0.018
Certification	-	-	Floorscore®

CE MARKING

	EN 14041	-	   
---	----------	---	---