

SURFACE PROTECTION

- These products have an embossed protective polyurethane surface treatment applied during the manufacturing process. It is therefore usually not necessary to seal or polish these products over their complete lifetime, greatly reducing the maintenance costs overall.
- The use of weight dispersing aids under heavy furniture is recommended in order to avoid permanent flooring indentation.
- The use of mats in doorways significantly reduces the amount of dirt and grit which could damage the new flooring.
- **Rubber leaves indelible stains on vinyl flooring.** Avoid placing waxed or rubber products in prolonged contact with your Texline floor.

INITIAL CLEAN

- Remove loose dirt and debris from the newly installed floor using broom or vacuum. Ensure all adhesive residues are removed with due regard to supplier's recommendations. Do not use high abrasive pads or scourers.
- Wash floor with a neutral detergent by low speed scrubbing machine fitted with nylon brushes or red pad. Ensure all detergent residues are rinsed and removed from the floor.

DAILY MAINTENANCE

- Remove loose dirt with broom or vacuum; damp mop with neutral detergent.

PERIODIC MAINTENANCE

- Machine auto scrub with nylon brush as required or wash floor and buff with red pad at 450rpm.

If you have any queries about the care and maintenance of your Texline floor, please contact Gerflor customer service.

