

**DESCRIPTION**

Total thickness	EN 428	mm	6.00
Thickness of wearlayer	EN 429	mm	2.00
Weight	EN 430	g/m <sup>2</sup>	9380
Tile size	EN 427	mm	635 x 635



**CLASSIFICATION**

Norm / Product specification	-	-	EN 649
European classification	EN 685	class	
K rating	-	class	
Fire rating / Critical flux	EN ISO 9239-1	kW/m <sup>2</sup>	9.66
Fire rating / Smoke density	EN ISO 9239-1	% min	212
Static electrical propensity	EN 1815	kV	≤ 2
Slip resistance wet : Pendulum	AS/NZ 4586 appendix a	-	
Slip dry resistance : Coefficient of friction	AS/NZ 4586 appendix b	-	
Slip resistance wet : ramp test	AS/NZ 4586 appendix c	-	
Slip resistance wet: ramp test with oil	AS/NZ 4586 appendix d	-	

**PERFORMANCE**

Wear resistance	EN 660.2	mm <sup>3</sup>	≤ 2
Wear group	EN 649	-	T
Dimensional stability	EN 434	%	≤ 0.25
Shore hardness	EN ISO 868	H <sub>D</sub>	≥ 50
Thermal conductivity	EN 12524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	-	OK
Surface treatment	-	-	PUR

**CE MARKING**

	EN 14041	-	
		-	